

*HD 3050mm Steel or Polymer  
Straight Blade Snowplough  
Height : 840mm, 900mm or 1200mm*

James A.  
**Cuthbertson**  
Limited



*3050 x 1200 Steel c/w  
Spring mounted rubbers*

*High Speed 5 Stud Hub  
And Foam Filled Tyre*



*Optional 3 Stage Marine  
Spec Power Angling Rams*

Station Road, Biggar,  
Lanarkshire, ML12 6DQ.  
Telephone: 01899 220020,  
[www.jamescuthbertson.co.uk](http://www.jamescuthbertson.co.uk)

## **HD STRAIGHT BLADE, REVERSIBLE SNOWPLOUGH** **SPECIFICATION**

### ***General***

#### ***Description.***

- HD reversible blade 3.050 metres wide.
- Top and bottom 'Y' brackets to suit WM1A fitting.
- Long stay bar for adjustment to allow left or right snow shedding.
- Spring mounted galvanised carrier plate.
- Fully galvanised wear edge clamp strip.

### ***Heights***

#### ***Available.***

- 840mm, 900mm or 1,200mm

### ***Construction.***

- All steel or steel skeleton c/w polymer breast plate construction.
- Breast plate fabricated from 3mm thick plate steel or 8mm polymer.
- Skeletal ribs fabricated from 6mm plate steel.
- Heel plate fabricated from 120mm x 60mm RHS.

NB. Heel plate fabricated from 120mm x 80mm RHS on power angling snowploughs.

### ***Wearing Edges.***

- 200 x 25mm section rubber edges. (840mm & 900mm high)
- 200 x 50mm section rubber edges. (1,200mm high)

### ***Plough Wheels.***

- Screw adjustable castor assemblies fitted with HD 5 stud hubs and 400 x 4 x 8 ply foam filled tyres to allow high speed 'ploughing.

OR

- HD 200mmØ, 360°, height adjustable, sealed ball bearing castors.

### ***Paint Finish.***

- All steelwork fully shot blasted prior to painting.
- One coat of two pack zinc rich primer.
- Two coats of two pack polyurethane gloss top coat.
- Customer specified colour.

NB. Polymer breast plate self coloured in high visibility orange.

### ***Options***

#### ***Available.***

- Din (N° 3 or N°5) - WM1A Interface complete with D.A. ram.
- 3 stage, marine specification power angle rams to allow remote left/right slewing from cab.
- Anti-spray curved top extension.
- Galvanised blade support legs.
- Edge marker poles.