3 Point Linkage Tractor Gritter.





Free Flowing Auger Outlet & Symmetric / Asymmetric Control





1m3 Gritter and 1.5m3 Gritter

Station Road, Biggar, Lanarkshire, ML12 6DQ. Telephone: 01899 220020, www.jamescuthbertson.co.uk



1m³ TRACTOR GRITTER SPECIFICATION 3 Point Linkage Mount Hydraulically powered from tractor hydraulics (BS1622: 1989 Class B)

Hopper.

• 2200mm x 1080mm x 1450mm (L x W x H, based on 1m³ unit) Fabricated from 3mm thick steel. Framework fabricated from RHS steel. Continuously welded at all joints.

Legs.

• Yard standing legs at front & rear.

Chutes, Spinner Cover,

• Formed stainless steel sheet delivery chute & hot dip galvanised spinner cover.

Spinner.

• Polymer spinner with bolt on stainless steel flights powered by hydraulic motor.

Salt Delivery System.

• Stainless steel auger, 100mm Ø.

Paint Finish.

• One coat of two pack zinc rich primer and two coats of two pack polyurethane finish to customer colour requirements.

Drive System.

• Hydraulic via tractor hydraulic drive system. Auger and spinner controlled through gritter mounted independent valve.

Controls.

- Control to hydraulic valve via 2 ~ morse cables operated by lever type handles with stops to set conveyor and spinner speeds, spread.
- Spread width adjustable between 0~11 metres.
- Discharge rate 10~40g/m².

Standard Equipment.

- Coupling to allow connection to tractor hydraulic system.
- All electrical cables routed in UPVC conduit.
- Guarding to exposed and moving parts.
- Spreading sign on rear (to BS.1622,1989).
- Rear lights & reflectors to meet current road vehicles regulations.
- High visibility rear chevrons to meet chapter 8 conspicuity requirements.

Optional Equipment.

- Hopper extension (capacity increased to 1.5m³ or 2.0m³).
- Hot-dip galvanized steel 50mm x 50mm weldmesh gritter cover.
- Amber warning beacon to rear of hopper.
- Weatherproof canopy.