Reversible Snow Plough for Suitable 4x4 Vehicles.





Left / Right Slew, Power Angling, In Cab Operation Option Available.





"Cubby" plate remains on the vehicle to allow the quick attachment of the snowplough.

Station Road, Biggar, Lanarkshire, ML12 6DQ. Telephone: 01899 220020, www.jamescuthbertson.co.uk



4 x 4 STRAIGHT BLADE SNOWPLOUGH SPECIFICATION

General Description.

- Reversible blade snowplough.
- Top & Bottom 'Y' bracket c/w mounting interface plate.
- Long stay bar for adjustment to allow left or right snow shedding.
- D.A. hydraulic ram.
- Hydraulic hoses c/w Q.R. couplings.
- Galvanised carrier plate.
- Galvanised wear edge clamp strip.
- Outer edge markers

Hydraulic Control.

• 12v electro hydraulic, double acting power pack c/w in-cab controls

Sizes Available.

• 1,830mm x 600mm

Construction.

- All steel or steel skeleton c/w polymer breast plate construction.
- Breast plate fabricated from 3mm thick plate steel or 8mm polymer.
- Skeletal ribs fabricated from 6mm plate steel.

Wearing Edges.

• 200 x 25mm section rubber edges.

Plough Wheels.

• HD 200mmØ, 360°, height adjustable, sealed ball bearing castors.

Mounting Frame.

- Chassis bracket for suitable 4 x 4.
- Snowplough mounting plate.

Paint Finish.

- All steelwork fully shot blasted prior to painting.
- One coat of two pack zinc rich primer.
- Two coats of two pack polyurethane gloss top coat.
- Customer specified colour.

NB. Polymer breast plate self coloured in high visibility orange.

Options Available.

• Power angle rams to allow remote left/right slewing from cab.