

Tractor Mount Straight Blade Snowplough

James A. **Cuthbertson**
Limited



3 Point Linkage or Chassis
Bracket Mount Available



Sizes Available From
1384mm x 600mm

Station Road, Biggar,
Lanarkshire, ML12 6DQ.
Telephone: 01899 220020,
www.jamescuthbertson.co.uk

TRACTOR MOUNT STRAIGHT BLADE SNOWPLOUGH **SPECIFICATION**

- General Description.**
- Reversible blade snowplough.
 - Bottom 'Y' bracket and adjustable top linkage. (Larger plough only)
 - Long stay bar for adjustment to allow left or right snow shedding.
 - Galvanised carrier plate.
 - Galvanised wear edge clamp strip.
- Sizes Available.**
- 2,668mm (2,440mm at rubbers) x 830mm
 - 1,384mm x 600mm
 - 1,575mm x 600mm
 - 1,830mm x 600mm
 - 2,135mm x 600mm
- Construction.**
- All steel or steel skeleton c/w polymer breast plate construction.
 - Breast plate fabricated from 3mm thick plate steel or 8mm polymer.
 - Skeletal ribs fabricated from 6mm plate steel.
- Wearing Edges.**
- 25mm section rubber edges.
- Plough Wheels.**
- Screw adjustable castor assemblies fitted with HD 5 stud hubs and 400 x 4 x 8 ply foam filled tyres to allow high speed 'ploughing.
- OR
- HD 200mmØ, 360°, height adjustable, sealed ball bearing castors.
- Mounting Frame.**
- Suitable for mounting on Cat 2, 3point linkage.
- Or
- Tractor mounting bracket c/w S.A. hydraulic ram.
- Or
- WM1A or DIN compatible.
- Paint Finish.**
- All steelwork fully shot blasted prior to painting.
 - One coat of two pack zinc rich primer.
 - Two coats of two pack polyurethane gloss top coat.
 - Customer specified colour.
- NB. Polymer breast plate self coloured in high visibility orange.
- Options Available.**
- Power angle rams to allow remote left/right slewing from cab.
 - Edge marker poles.